

Abraxan 95 Spray

K P 2 N -30

INTERSPARE Lubricants-Special grease spray

Abraxan 95 Spray is a complex soap grease resistant to water and alkali. Due to its high pressure absorbing capacity in comparison to conventional lubricants **Abraxan 95 Spray** achieves a reliability of operation being above the average.

Abraxan 95 Spray does not tend to lumping also at longer use.

TECHNICAL DATA

Abraxan 95 Spray

Colour	beige
Temperature range Short time	-35°C to +150°C up to +160°C
Thickener	Ca-Complex soap
Base oil	PAO/mineral oil
Base oil viscosity DIN 51562 at 40°C	approx. 100 mm ² /s
Consistency class DIN 51818	2
Worked penetration DIN ISO 2137	265 - 295
Dropping point DIN ISO 2176	>300
Corrosion protection (Emscor) DIN 51802	0 - 0
Four ball test value (VKA) DIN 51350	2400 N / 2600 N

USES

Universal high performance grease spray for the textile- industry, with recommenddation from HARRY LUCAS GMBH, Neumünster.

Abraxan 95 Spray is also exceptionally used as corrosion protection and as conservation of metallic parts at sea transport.

PACKING

400 ml spray

MADE IN GERMANY

- all rights reserved -